

Spezifikationen		<b>boxed 2.0</b>		
Modellreihe		C60	C30	C40
Typ		C60	C30	C40
CPU	CPU-Board			
	Low-Power-CPU	i3-i7 (Gen. 6/7) (TPD max. 35W)	Celeron 3955U (oB)	Celeron 3955U (oB)
Speich.	RAM Slots	1	1	2
	Max. RAM (GB)	16	16	32
Schnittstellen	COM	2	6	2
	LAN	5	2	5
	LAN / PoE	-	-	-
	USB	4	7	4
Audio/Video	VGA	x	x	-
	DVI	-	x	-
	HDMI	x	-	x
	DP	-	-	-
	Audio	-	-	-
Steckpl.	mPCIe / M.2 Slot	1x mPCIe	1x mPCIe	1x mPCIe
	PCIe / PCI Slot	1x PCIe	1x PCIe	1x PCIe
Betriebstemp. (Low-P.-CPU + SSD)		70°C (mSATA SSD)	70°C (mSATA SSD)	70°C (mSATA SSD)
Abmessg.	H (mm)	210	210	210
	B (mm)	77	77	77
	T (mm)	125	125	125
Wireless	SIM-Karte	1	1	1
	WLAN/WiFi	o	o	o
	Bluetooth	o	o	o
	GPS	o	o	o
9 - 36 VDC		x	x	x
Montage	VESA-Befestigung	75 x 75	75 x 75	75 x 75
	Wandmontage	o	o	o
	Gewicht	1,9 kg	1,9 kg	1,9 kg
	Volumen (ccm)	2000		
Artikelnr.		b2.0-C60	b2.0-C30	b2.0-C40

x = vorhanden, - = nicht vorhanden, o = optional, oB = on Board, Gen = CPU-Generation

Technische Änderungen vorbehalten

