

# UNIVERSAL Large Displays 1L10C and 2L10C



EZMR-1L10C



EZMR-2L10C



EZMT-1L10C



EZMT-2L10C

EZMarquee Specifications (UNIVERSAL)				
Part Number	EZMR-1L10C EZMR-1L10C-E EZMR-1L10C-D EZMR-1L10C-P	EZMT-1L10C EZMT-1L10C-E EZMT-1L10C-D EZMT-1L10C-P	EZMT-1L10C EZMT-1L10C-E EZMT-1L10C-D EZMT-1L10C-P	EZMR-2L10C EZMR-2L10C-E EZMR-2L10C-D EZMR-2L10C-P
Displaytype	RED LED	TRI-Color LED	RED LED	TRI-Color LED
Specification	1 Line of 10 Char (2")		2 Lines of 10 Char (2")	
Max View. Distance	100 Feet with 2" Characters		200 Feet with 4" Characters	
Power Consumption	8 VA	14 VA	15 VA	28 VA
Approvals	CE, UL, CUL			
Enclosure	IP 54/NEMA 12			
Operating Temp.	0° to 60° C Ambient			
Storage Temp.	-40° to 95° C Ambient			
Humidity	10% to 95%, Non-Condensing			
Input Power	90 to 230 VAC, 47-63Hz			
Electrical Interference	NEMA ICS 2-230 Showering Arc Test			
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis			
Shock	10G for under 12ms in the X, Y, and Z axis			
Serial Communication	RS232; RS422/485			
Add. Ports (Option)	Ethernet, Devicenet, Profibus			
External Dimensions	479 x 121 x 70 mm		479 x 156 x 70 mm	
Weight	1,3 Kg	1,4 Kg	2,3 Kg	2,4 Kg