

# OUTDOOR Large Displays 1L20C and 1L40C

1 Line of 2", 20 Cha

EZMR-1L20C-OUT  
EZMRH-1L20C-OUT

1 Line of 2", 20 Cha

EZMT-1L20COUT

1 Line of 2", 40 Characters Per line

EZMR-1L40C-OUT  
EZMRH-1L40C-OUT

1 Line of 2", 40 Characters Per line

EZMT-1L40C-OUT

## EZMarquee Specifications (OUTDOOR)

Part Number	EZMR-1L20C-OUT EZMR-1L20C-E-OUT EZMR-1L20C-D-OUT EZMR-1L20C-P-OUT EZMRH-1L20C-OUT EZMRH-1L20C-E-OUT EZMRH-1L20C-D-OUT EZMRH-1L20C-P-OUT	EZMT-1L20C-OUT EZMT-1L20C-E-OUT EZMT-1L20C-D-OUT EZMT-1L20C-P-OUT	EZMR-1L40C-OUT EZMR-1L40C-E-OUT EZMR-1L40C-D-OUT EZMR-1L40C-P-OUT EZMRH-1L40C-OUT EZMRH-1L40C-E-OUT EZMRH-1L40C-D-OUT EZMRH-1L40C-P-OUT	EZMT-1L40C-OUT EZMT-1L40C-E-OUT EZMT-1L40C-D-OUT EZMT-1L40C-P-OUT
Outdoor Model	RED LED	TRI-Color LED	RED LED	TRI-Color LED
High-bright Model	RED Sunlight Readable 8000 nits		RED Sunlight Readable 8000 nits	
Specification	1 Line of 20 Char (2")		1 Lines of 40 Char (2")	
Max. Viewable Distance	100 Feet with 2" Characters			
Power	15 watts	28 watts	30 watts	60 watts
Approvals	UL, CUL, CE			
Enclosure	NEMA 4X			
Operating Temp.	-20° to 60° C Ambient			
Storage Temp.	-40° to 95° C Ambient			
Humidity	10% to 95% RH, Non-Condensing			
Input Power	110/220 VAC, 47-63Hz			
Electrical Interference	NEMA ICS 2-230 Showering Arc Test			
Electrical Tolerance	ANSI C37.90a-1974 (SWC) Surge With-Stand Capability Test			
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis			
Shock	10G for under 12ms in the X, Y, and Z axis			
Serial Comm.	Port 1 RS232; Port 2 RS422/485			
External Dim.	36.9" x 4.8" x 2.8" (936.44 x 121.43 x 69.85mm)		72.1" x 5.4" x 2.8" (1831.31 x 106.35 x 69.85mm)	
Weight	4.5 lbs	4.8 lbs	8 lbs	8.5 lbs