

OUTDOOR Large Displays 2L20C and 2L40C



EZMR-2L20C-OUT EZMRH-2L20C-OUT



EZMT-2L20C-OUT



EZMR-2L40C-OUT EZMRH-2L40C-OUT



EZMT-2L40C-OUT

EZMarquee Specifications (OUTDOOR)

Part Number	EZMR-2L20C-OUT EZMR-2L20C-E-OUT EZMR-2L20C-D-OUT EZMR-2L20C-P-OUT EZMRH-2L20C-OUT EZMRH-2L20C-E-OUT EZMRH-2L20C-D-OUT EZMRH-2L20C-P-OUT	EZMT-2L20C-OUT EZMT-2L20C-E-OUT EZMT-2L20C-D-OUT EZMT-2L20C-P-OUT	EZMR-2L40C-OUT EZMR-2L40C-E-OUT EZMR-2L40C-D-OUT EZMR-2L40C-P-OUT EZMRH-2L40C-OUT EZMRH-2L40C-E-OUT EZMRH-2L40C-D-OUT EZMRH-2L40C-P-OUT	EZMT-2L40C-OUT EZMT-2L40C-E-OUT EZMT-2L40C-D-OUT EZMT-2L40C-P-OUT
Outdoor Model	RED LED	TRI-Color LED	RED LED	TRI-Color LED
High-bright Model	RED Sunlight Readable 8000 nits		RED Sunlight Readable 8000 nits	
Specification	2 Lines of 20 Char (2")		2 Lines of 40 Char (2")	
Max. View Dist.	200 Feet with 4" Characters			
Power	30 watts	55 watts	54 watts	100 watts
Approvals	UL, CUL, CE (File no. E209355)			
Enclosure	NEMA 4X			
Operating Temp.	-20° to 60° C Ambient			
Storage Temp.	-40° to 95° C Ambient			
Humidity	10% to 95% RH, Non-Condensing			
Input Power	110/220 VAC, 47-63Hz			
Electrical Interference/Tolerance	NEMA ICS 2-230 Showering Arc Test ANSI C37.90a-1974 (SWC) Surge With-Stand Capability Test			
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis			
Shock	10G for under 12ms in the X, Y, and Z axis			
Serial Comm.	RS232/422/485			
External Dim.	36.86" x 5.67" x 2.75" (936.44 x 144.02 x 69.85mm)		72.1" x 5.67" x 2.75" (1831.31 x 144.02 x 69.85mm)	
Weight	8 lbs	8.5 lbs	15 lbs	16 lbs