

UNIVERSAL Large Displays 1L10C and 2L10C



EZMR-1L10C



EZMR-2L10C



EZMT-1L10C



EZMT-2L10C

EZMarquee Specifications (UNIVERSAL)				
Part Number	EZMR-1L10C EZMR-1L10C-E EZMR-1L10C-D EZMR-1L10C-P	EZMT-1L10C EZMT-1L10C-E EZMT-1L10C-D EZMT-1L10C-P	EZMT-1L10C EZMT-1L10C-E EZMT-1L10C-D EZMT-1L10C-P	EZMR-2L10C EZMR-2L10C-E EZMR-2L10C-D EZMR-2L10C-P
Displaytype	RED LED	TRI-Color LED	RED LED	TRI-Color LED
Specification	1 Line of 10 Char (2")		2 Lines of 10 Char (2")	
Max View. Distance	100 Feet with 2" Characters		200 Feet with 4" Characters	
Power Consumption	8 VA	14 VA	15 VA	28 VA
Approvals	CE, UL, CUL			
Enclosure	IP 54/NEMA 12			
Operating Temp.	0° to 60° C Ambient			
Storage Temp.	-40° to 95° C Ambient			
Humidity	10% to 95%, Non-Condensing			
Input Power	90 to 230 VAC, 47-63Hz			
Electrical Interference	NEMA ICS 2-230 Showering Arc Test			
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis			
Shock	10G for under 12ms in the X, Y, and Z axis			
Serial Communication	RS232; RS422/485			
Add. Ports (Option)	Ethernet, Devicenet, Profibus			
External Dimensions	479 x 121 x 70 mm		479 x 156 x 70 mm	
Weight	1,3 Kg	1,4 Kg	2,3 Kg	2,4 Kg

UNIVERSAL Large Displays 1L20C and 1L40C



EZMR-1L20C



EZMT-1L20C



EZMR-1L40C



EZMT-1L40C

EZMarquee Specifications (UNIVERSAL)

Part Number	EZMR-1L20C EZMR-1L20C-E EZMR-1L20C-D EZMR-1L20C-P	EZMT-1L20C EZMT-1L20C-E EZMT-1L20C-D EZMT-1L20C-P	EZMR-1L40C EZMR-1L40C-E EZMR-1L40C-D EZMR-1L40C-P	EZMT-1L40C EZMT-1L40C-E EZMT-1L40C-D EZMT-1L40C-P
Displaytype	RED LED	TRI-Color LED	RED LED	TRI-Color LED
Specification	1 Line of 20 Char (2")		1 Lines of 40 Char (2")	
Max View. Distance	100 Feet with 2" Characters			
Power Consumption	15 VA	28 VA	30 VA	60 VA
Approvals	CE, UL, CUL			
Enclosure	IP 54/NEMA 12			
Operating Temp.	0° to 60° C Ambient			
Storage Temp.	-40° to 95° C Ambient			
Humidity	10% to 95%, Non-Condensing			
Input Power	90 to 230 VAC, 47-63Hz			
Electrical Interference	NEMA ICS 2-230 Showering Arc Test			
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis			
Shock	10G for under 12ms in the X, Y, and Z axis			
Serial Communication	RS232; RS422/485			
Add. Ports (Option)	Ethernet, Devicenet, Profibus			
External Dimensions	936 x 121 x 70 mm		1831 x 106 x 70 mm	
Weight	2,0 Kg	2,2 Kg	3,6 Kg	3,8 Kg

UNIVERSAL Large Displays 2L20C and 2L40C



EZMR-2L20C



EZMT-2L20C



EZMR-2L40C



EZMT-2L40C

EZMarquee Specifications (UNIVERSAL)

Part Number	EZMR-2L20C EZMR-2L20C-E EZMR-2L20C-D EZMR-2L20C-P	EZMT-2L20C EZMT-2L20C-E EZMT-2L20C-D EZMT-2L20C-P	EZMR-2L40C EZMR-2L40C-E EZMR-2L40C-D EZMR-2L40C-P	EZMT-2L40C EZMT-2L40C-E EZMT-2L40C-D EZMT-2L40C-P
Displaytype	RED LED	TRI-Color LED	RED LED	TRI-Color LED
Specification	2 Line of 20 Char (2")		2 Lines of 40 Char (2")	
Max View. Distance	200 Feet with 4" Characters			
Power Consumption	30 VA	55 VA	54 VA	100 VA
Approvals	CE, UL, CUL			
Enclosure	IP 54/NEMA 12			
Operating Temp.	0° to 60° C Ambient			
Storage Temp.	-40° to 95° C Ambient			
Humidity	10% to 95%, Non-Condensing			
Input Power	90 to 230 VAC, 47-63Hz			
Electrical Interference	NEMA ICS 2-230 Showering Arc Test			
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis			
Shock	10G for under 12ms in the X, Y, and Z axis			
Serial Communication	RS232; RS422/485			
Add. Ports (Option)	Ethernet, Devicenet, Profibus			
External Dimensions	936 x 156 x 70 mm		1831 x 144 x 70 mm	
Weight	3,6 Kg	3,8 Kg	6,8 Kg	7,2 Kg

UNIVERSAL Large Displays 4L20C and 4L40C



EZMR-4L20C



EZMT-4L20C



EZMR-4L40C



EZMT-4L40C

EZMarquee Specifications (UNIVERSAL)

Part Number	EZMR-4L20C EZMR-4L20C-E EZMR-4L20C-D EZMR-4L20C-P	EZMT-4L20C EZMT-4L20C-E EZMT-4L20C-D EZMT-4L20C-P	EZMR-4L40C EZMR-4L40C-E EZMR-4L40C-D EZMR-4L40C-P	EZMT-4L40C EZMT-4L40C-E EZMT-4L40C-D EZMT-4L40C-P
Displaytype	RED LED	TRI-Color LED	RED LED	TRI-Color LED
Specification	4 Line of 20 Char (2")		4 Lines of 40 Char (2")	
Max View. Distance	400 Feet with 8" Characters			
Power Consumption	55 VA	100 VA	100 VA	180 VA
Approvals	CE, UL, CUL			
Enclosure	IP 54/NEMA 12			
Operating Temp.	0° to 60° C Ambient			
Storage Temp.	-40° to 95° C Ambient			
Humidity	10% to 95%, Non-Condensing			
Input Power	90 to 230 VAC, 47-63Hz			
Electrical Interference	NEMA ICS 2-230 Showering Arc Test			
Vibration	5 - 55 Hz 2G for 2 hours in the X, Y, and Z axis			
Shock	10G for under 12ms in the X, Y, and Z axis			
Serial Communication	RS232; RS422/485			
Add. Ports (Option)	Ethernet, Devicenet, Profibus			
External Dimensions	929 x 298 x 70 mm		1840 x 298 x 70 mm	
Weight	6,8 Kg	7,2 Kg	13,60 Kg	14,5 Kg